

SEV 34

NEW 5 YEAR
WARRANTY
ON FLECK CONTROL VALVES

Water Softener

Commercial Automatic

Est: 1987



To us it's more than just water...

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

Type	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	34,000 litres at 100 mg/l hardness	
Media Tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Resin Capacity	56 litres of fine mesh cation resin	
Control Valve	Fleck 5800 electronic 5 stage regeneration fully adjustable functions Microprocessor control	
Brine Tank	18" (46cm) x 40" (102cm) with lid	
Flow Rate	Continuous	40 litres per minute
	Peak	50 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	3/4" (20mm)
	Drain	1/2" (15mm)
Salt Usage	8kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Water Filters Pty Ltd
Unit 2, 44 Hutton St, Osborne Park WA 6017
Telephone 08 6156 0220
Email: sales@waterfilter.com.au
www.wawaterfilters.com.au