



Reduction Claim

Sediments	✓
Chlorine	✓
Pesticides & Herbicides	✓
Flammable Liquids (VOCs)	✓
Taste, Odours & Colour	✓
Heavy Metals (Copper, Lead...)	✓
Parasites	✓
Bacteria & Viruses	✗
PFAS Compounds	✗

Replacement Filters Bundle

*Prices are subject to change without any prior notice.

SPECIFICATIONS

Dimensions: 270 W x 370 H x 130 D mm
 Operating Pressure: 200-600 kPa
 Operating Temperature: 0.6°C - 38°C
 Flow Rate: 3 LPM
 Connection Type: Clip on Hose Connections

HOSE CONNECTORS

12mm Hose Fittings
 Have been specifically designed for quick and secure hose to tap connections.



CHOICE OF FILTERS



With Sediment and Carbon
\$250*



With Sediment and Disruptor®
\$295*

For PFOA & PFOS

Sediments	✓	✓
Chlorine	✓	✓
Pesticides & Herbicides	✓	✓
Flammable Liquids (VOCs)	✓	✓
Taste, Odours & Colour	✓	✓
Heavy Metals (Copper, Lead...)	✓	✓
Parasites	✓	✓
Bacteria & Viruses	✗	✓
PFAS Compounds	✗	✓

\$85*

\$125*



Components are Tested and Certified by NSF International under NSF/ANSI Standard 42 for material requirements only.

MAINTENANCE

To ensure optimal performance and hygiene and to prevent build up of contaminants, we recommend that filters are not used any longer than 12 months. However, replacement frequency also depends on water quality and usage.

A portable water filter designed to connect quickly and easily to your caravan or motor home.

CONNECTS TO STANDARD GARDEN HOSE FITTINGS

Clip on Hose Caravan Water Filtration Systems are designed to connect easily to garden hose fittings which are readily available in most locations.

MECHANICAL FILTRATION in the first stage

100% Polypropylene Triple Gradient Sediment Filters are essential in the first stage to capture sand, dirt, rust, algae, silt, mud and particles greater than 1 micron. The sediment filter will avoid premature blockages within the system and will extend the life span of the second stage filter.

LEAD REMOVAL in the second stage

The Carbon Filter and the Disruptor Filter in the second stage have specialised filtration media to remove lead and other heavy metals.

WATERMARK CERTIFIED SYSTEM AND NSF 42 CERTIFIED COMPONENTS.

Made with materials complying with NSF/ANSI Standard 42.

CAUTION: To reduce the risk of property damage due to water leakage:

- For Cold water use only. Install on COLD water lines only.
- Never install or operate where inlet water pressure may exceed 120 psi (827kPa)
- Protect from freezing. Remove filter if temperature drop below 1°C.

